



Thermo Scientific 1300 Series A2
Class II, Type A2 Biological Safety Cabinets

*Good for you,
good for the environment*

Thermo Scientific 1300 Series A2

Enjoy best-in-class performance and value



Superior Containment

Unique airflow design maximizes safety

Extremely Comfortable

Ergonomic design simplifies ease of use

Added Convenience

Choice of configuration increases flexibility



Optimizing Safety and Efficiency

Laboratories today are facing new challenges. Safety and reliability continue to be paramount. Yet, there is growing need for improved energy efficiency, simpler operation and less maintenance.

Our Thermo Scientific 1300 Series A2 Class II, Type A2 biological safety cabinets provide best-in-class safety, ergonomics and energy efficiency for today's most demanding laboratory applications.

4 foot 1300 Series A2 biological safety cabinet with one-piece, stainless steel interior and optional electric stand


1300

Series A2

The Thermo Scientific 1300 Series A2 is backed by our global reputation and commitment to provide the safest and most reliable biological safety cabinets available.

We have decades of market leadership in biological safety cabinets, as well as a full suite of laboratory solutions – all with unmatched quality and world-renowned service and support.





Ergonomic Design for Ease-of-Use

More Flexibility for Added Convenience

One-piece stainless steel interior is now available as an alternative to our coated interior cabinets. Select either the manual or electric adjustable stand for increased flexibility.

Ergonomic Design Enhances Safety

Sloped Front

Cabinet front is sloped 10° for enhanced comfort and reduced operator fatigue.

Reduced Noise Level

Lower noise level enhances the attention and allows user to focus on work without distraction.

Spacious Work Area

The large, unobstructed work surface increases productivity and safety.

Single-Piece Work Tray

The flat, single-piece stainless steel work tray supports ease of cleaning.

Comfortable Armrest

Armrests sit just above the intake grill to enable farther reach inside the cabinet while maintaining safe airflows.



Two Choices of Cabinet Interior

The 1300 Series A2 biological safety cabinet is available with a painted cabinet interior which provides a glare-free working environment, or with a seamless one-piece side and rear wall stainless steel interior configuration.

Easy-to-Access Control Panel and Performance Data

The large control panel displays valuable safety and performance data, and is within easy view and reach from a seated position. The intuitive interface delivers a constant read-out of downflow and inflow velocities and overall cabinet performance status.

All models of the Thermo Scientific 1300 Series A2 have been fully tested and verified to meet NSF/ANSI 49 for Class II, Type A2 conditions.



Ease-of-Use for Enhanced Safety

An efficient working environment can eliminate expensive disruptions to lab procedures. Our Thermo Scientific 1300 Series A2 delivers easy-to-use features that enable you to perform your best work – productively and safely.

SmartClean™ Window Design

To reduce risk of sample contamination, our patented window design easily lowers for thorough cleaning of the window's inner surface. This unique design protects the operator by maintaining inflow even when the window is lowered.

Easy Servicing


Fan control and power supply can be replaced independently of the DC motor with no need for disruptive decontamination of the cabinet. All cabinet components, including HEPA filters, are easily accessible from the front to allow for rapid service and minimal work disruption. The SmartClean window design simplifies access to the downflow filter during annual certification.

Exceptional Safety

Smooth components are used throughout the cabinet, virtually eliminating the risk of injury during routine cleaning, servicing and maintenance procedures.

Worry-free Decontamination

The easy to use, optional UV light is programmable from 30 minutes to 24 hours in 30-minute increments, extending bulb life and saving energy.



Hour Counter & Airflow Read-Out:

Clearly displays critical safety and real-time performance data including inflow and downflow velocities and hours of operation

Patented Performance Factor:

Displays real-time information of overall cabinet status including operation safety and service requirements

Front Window Status:

Visual and audible alarm indicates whether front window is in correct working position

Operating Speed Airflow Indicator:

Audible and visual alarms indicate when airflow is safe or restricted

Energy-Savings Airflow Indicator:


Displays reduced speed operation when front window is closed

Good for you, good for the environment

Thermo Scientific 1300 Series A2 features advancements in brushless DC motor technology for dramatically improved energy efficiency, safety performance and reliability. We pioneered the use of brushless DC motors in our biological safety cabinets in 2002, and now use them across our full line.

DC motors —

- *reduce energy costs*
- *increase reliability*
- *reduce air conditioning costs*
- *optimize environmental protection*



Thermo Scientific biological safety cabinets are available in the broadest selection of energy saving models for any application or budget. Visit www.thermo.com/bsc to learn more about the independent validation of our energy saving calculations.


Independent **Safety** Systems for Unmatched **Security**

SmartFlow™ maintains a safe working environment.

The 1300 Series A2 employs a unique airflow system that raises safety and containment to a new level. Independent supply and exhaust blowers automate balancing of downflow and inflow/exhaust velocities to ensure continuous safe working conditions. Our smart DC motors monitor and control fan speed in real-time to maintain user protection at the access opening, even as the filters load or the line voltage fluctuates.

Digital Airflow Verification (DAVe) validates product and personnel protection.


Independent pressure sensors detect changes in pressure across the exhaust and downflow plenums. An alarm signals when a 20% change in inflow/exhaust or downflow occurs to alert the user if safety is compromised. Airflow velocities are displayed on the control panel for monitoring and recording.



Night-set-back mode saves energy while maintaining a clean work area.

When the front sash is closed, our intelligent speed control automatically reduces blower speed to 30%, extending HEPA filter life and ensuring a sterile working environment even when the cabinet is not in use.

This reduced flow mode uses only <40W (4 foot cabinet) to operate, and is >75% more energy efficient than similar features on other biological safety cabinets.



Thermo Scientific 1300 Series A2

Ordering Information for Options and Accessories

Part No.	Description	Application	Additional Comments	Factory Installed
1911302	Manual adjustable stand for 4 foot cabinet	Provides comfortable work surface height of 30" (750 mm) to 37" (950 mm) adjustable in 1" increments for seated or standing applications.	<i>This accessory is included in the 1300 Series packages.</i>	
1911303	Manual adjustable stand for 6 foot cabinet			
50119126	Electric adjustable stand for 4 foot cabinet (120V)	Provides infinite adjustability for comfortable work surface height of 30" (750 mm) to 37" (950 mm)		
50119128	Electric adjustable stand for 6 foot cabinet (120V)			
1911322	Rolling castor stand for 4 foot cabinet	Provides comfortable fixed work surface height of 34" (860 mm) for seated applications.	<i>Designed for limited mobility of the cabinet for cleaning purposes.</i>	
1911346	Rolling castor stand for 6 foot cabinet			
1911319	UV light option for 4 foot cabinet	Provides safe and easy method for cabinet disinfection.	<i>This accessory is included in the 1300 Series packages.</i>	x
1911368	UV light option for 6 foot cabinet			x
1911313	Stainless steel armrest (set of 2)	Provides ergonomic forearm support and extended reach inside the cabinet with less airflow disruption.	<i>This accessory is included in the 1300 Series packages.</i>	
1911308	Combustible gas valve	Rated for combustible gas dispensing inside the cabinet chamber.	<i>The service valve for standard applications offers a long stem pipe fitting and is appropriate for side access media services. For bottom, top or rear access, refer to the Universal Piping options listed below for use with the short stem valves.</i>	
1911309	Non-combustible gas valve	Rated for non-combustible gas dispensing inside the cabinet chamber.		
1911310	Vacuum valve	Rated for routing vacuum inside the cabinet chamber.		
1911311	Water valve	Rated for water dispensing inside the cabinet chamber.		
1911312	IV bag holder kit with 12 hooks	Provides bar and hooks to hang IV bags near the interior ceiling of the cabinet.		
191127	Adjustable footrest	For ergonomic foot and posture support during seated use.		
1911316	Thimble duct exhaust transition for 4 foot cabinet	Allows the biological safety cabinet to be connected to an external exhaust for the removal of volatile toxic chemicals or radionuclides used in the cabinet.	<i>The thimble duct exhaust connection is the method recommended by NSF/ANSI 49 for externally exhausting the Class II, Type A2 biological safety cabinet.</i>	
1911317	Thimble duct exhaust transition for 6 foot cabinet			
1911321	Universal piping for models 1355 and 1385, right side	Allows air and gas service to be piped through the top, sides, or bottom of the cabinet to minimize the side-to-side footprint of the cabinet's utility piping. Two pre-plumbed service ports per side only.	<i>User must select which side of the cabinet requires piping routed through the side wall. Select Right or Left Side as you stand in front, facing the cabinet. Selection must be made at the time of order.</i>	x
1911369	Universal piping for models 1355 and 1385, left side			x
1911367	Universal piping for models 1357 and 1387, right side			x
1911370	Universal piping for models 1357 and 1387, left side			x
1911381	Universal piping for models 1345 and 1375, right side			x
1911382	Universal piping for models 1345 and 1375, left side			x
1911389	Universal piping for models 1345 and 1375, both sides			x
1911383	Universal piping for models 1347 and 1377, right side			x
1911384	Universal piping for models 1347 and 1377, left side	x		
1911391	Universal piping for models 1347 and 1377, both sides	x		
1911304	Combustible gas valve for universal piping option	Rated for combustible gas dispense inside the cabinet chamber.	<i>For use with Universal Piping options only. The Short piping stem on this valve will not penetrate the side wall of the cabinet.</i>	
1911305	Non-combustible gas valve for universal piping option	Rated for non-combustible gas dispense inside the cabinet chamber.		
1911306	Vacuum valve for universal piping option	Rated for routing vacuum inside the cabinet chamber.		
1911307	Water valve for universal piping option	Rated for water dispensing inside the cabinet chamber.		



Electric adjustable stand



Manual adjustable stand





Foot rest

Schematic Drawing 1300 Series A2

1300 Series A2: Designed for Class II, Type A2 applications

The 1300 Series A2 features HEPA-filtration with recirculation of the air inside the work chamber, creating a near particle-free environment – ideal for most microbiological and tissue culture applications. The 1300 Series A2 may be exhausted to the outside of the building using the optional thimble exhaust connection, providing a safe working environment when working with minute quantities of volatile toxic chemicals.



		A	B	C	D	E
seated work position minimum	mm	680				
seated work position minimum	inch	26.77				
standing work position minimum	mm	680				
standing work position minimum	inch	34.65				
		B	C	D	E	
1300 Series 1.2	mm	228	644	1300	1200	
1300 Series 1.2	inch	8.97	25.35	51.18	47.24	
1300 Series 1.8	mm	474.5	951	1900	1800	
1300 Series 1.8	inch	18.68	37.44	74.80	70.86	

Attention: With additional gas valves in the side walls, you must plan for more width (dimension D)



Stainless steel interior and armrests



Servicing taps (gas, water, vacuum) for side wall



Thimble duct exhaust transition

Thermo Scientific 1300 Series A2 Class II, Type A2 Biological Safety Cabinets



Specifications and Ordering Information		4 ft models		6 ft models	
Standard Model	Coated interior walls, cabinet only	1355	1356	1357	1358
Standard Package	Includes coated interior cabinet walls, manual adjustable height stand, factory installed UV light, and one set of armrests	1385	1386	1387	1388
Stainless Steel Model	One-piece stainless steel interior, cabinet only	1345	1346	1347	1348
Stainless Steel Package	Includes stainless steel interior cabinet walls, manual adjustable height stand, factory installed UV light, and one set of armrests	1375	1376	1377	1378
	Electrical Requirements for Standard and Stainless Steel	120V, 50/60Hz	230V, 50/60Hz	120V, 50/60Hz	230V, 50/60Hz
Dimensions	Exterior Dimensions H x W x D inches (mm)	61.8 x 51.2 x 31.5 (1568 x 1300 x 800)		61.8 x 74.8 x 31.5 (1568 x 1900 x 800)	
	Interior Dimensions H x W x D inches (mm)*	30.7 x 47.2 x 18.3 (780 x 1200 x 465)		30.7 x 70.9 x 18.3 (780 x 1800 x 465)	
	Working Height of Front Window inches (mm)	10 (254)		10 (254)	
	Maximum Opening Height of Front Window inches (mm)	21 (535)		21 (535)	
	Shipping Dimensions H x W x D inches (mm)	68.1 x 55.5 x 36.4 (1730 x 1410 x 925)		68.1 x 79.1 x 36.4 (1730 x 2010 x 925)	
Weight	Net Weight lbs (kg)	375 (170)		507 (230)	
	Shipping Weight lbs (kg)	430 (195)		584 (265)	
	Maximum Load of One-Piece Work Tray lbs (kg)	110 (50)		110 (50)	
Ventilation System	Exhaust/Inflow Air Volume CFM (m ³ /h)	342 (582)		513 (872)	
Heat Emission	Heat Emission at 25°C Ambient BTU/hr (kW)	683 (0.2)		1366 (0.4)	
Filter Specification	Supply/Exhaust Air Filter	H14 HEPA EN 1822 99.995% at the most penetrating particle size (mini-pleated)			
Performance	Certification	NSF/ANSI 49, UL		NSF/ANSI 49, UL	
	Sound Pressure Level dB (A)	63		65	
	Lighting Power (fc)	>120		>120	
Electrical Data	Power Consumption, Operating Set Point (kW)	0.2		0.4	
	Current Consumption (Amps)	2.3	1.2	3.6	1.9
	Branch Circuit Protection	T 15 Amp fuse or Class B 15 Amp circuit breaker is required. The local electrical regulations in the country of use as well as the relevant connection conditions must be observed.			
Supply Management	Receptacles	The receptacles have a load capacity of up to 5 A and are protected with T 5 A fuses. When all receptacles are in use simultaneously they must not exceed the maximum total load capacity of 5 A.			
Features	Access Ports 0.94" (24 mm) diameter	6 (3 on each side)			
	Service Valves	Up to 6 (installed through side wall access ports)			
	Receptacles (Rear Wall)	GFI Duplex, right side	Single, right side	GFI duplex, left and right side	Two single, left and right side
	Warranty	3 years			

* The depth of 465mm is the usable work area depth, not including the air intake grills.

© 2009 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

North America: USA/Canada +1 866 984 3766 (866-9-THERMO)

Europe: Austria +43 1 801 40 0, Belgium +32 2 482 30 30, France +33 2 2803 2180, Germany national toll free 08001-536 376, Germany international +49 6184 90 6940, Italy +39 02 02 95059 434-254-375, Netherlands +31 76 571 4440, Nordic/Baltic countries +358 9 329 100, Russia/CIS +7 (812) 703 42 15, Spain/Portugal +34 93 223 09 18, Switzerland +41 44 454 12 12, UK/Ireland +44 870 609 9203

Asia: China +86 21 6865 4588 or +86 10 8419 3588, India toll free 1800 22 8374, India +91 22 6716 2200, Japan +81 45 453 9220, Other Asian countries +852 2885 4613 **Countries not listed:** +49 6184 90 6940 or +33 2 2803 2180

www.thermo.com/bsc

Thermo
SCIENTIFIC